

Kurzreferenz SQL

CREATE DATABASE

```
CREATE [OR REPLACE] DATABASE [IF NOT EXISTS] db_name
```

DROP DATABASE

```
DROP DATABASE [IF EXISTS] db_name
```

USERS/PERMISSIONS

```
CREATE [OR REPLACE] USER [IF NOT EXISTS] 'user_name' IDENTIFIED BY 'password'  
GRANT ALL ON database.* TO 'user_name'  
REVOKE ALL ON database.* FROM 'user_name'  
DROP USER [IF EXISTS] 'user_name'
```

LOAD DATA

```
LOAD DATA LOCAL INFILE 'file_name' INTO TABLE tbl_name [FIELDS TERMINATED BY  
'string'] [ENCLOSED BY 'string'] [LINES TERMINATED BY 'string'] [IGNORE number  
ROWS]
```

CREATE TABLE

```
CREATE [OR REPLACE] TABLE [IF NOT EXISTS] tbl_name  
    (col_name [NOT NULL | NULL] [DEFAULT default_value | (expression)]  
    [AUTO_INCREMENT] [UNIQUE [KEY] | [PRIMARY] KEY], ... | FOREIGN KEY  
    (index_col_name, ... ) REFERENCES tbl_name (index_col_name, ... ))  
CREATE [OR REPLACE] TABLE [IF NOT EXISTS] tbl_name LIKE old_table_name
```

ALTER TABLE

```
ALTER TABLE tbl_name [ADD | MODIFY | DROP]      (col_name [NOT NULL | NULL] [DEFAULT  
default_value | (expression)]  
    [AUTO_INCREMENT] [UNIQUE [KEY] | [PRIMARY] KEY], ... | FOREIGN KEY  
    (index_col_name, ... ) REFERENCES tbl_name (index_col_name, ... ))
```

DROP TABLE

```
DROP TABLE [IF EXISTS] tbl_name
```

SELECT

```
SELECT [ALL | DISTINCT] select_expr [, select_expr ...]  
    [FROM table_reference  
    [[INNER | {LEFT|RIGHT} OUTER] JOIN table_reference ON join_condition]  
    [WHERE where_condition]  
    [GROUP BY {col_name | expr | position} [ASC | DESC], ...]  
    [ORDER BY {col_name | expr | position} [ASC | DESC], ...]]
```

INSERT

```
INSERT INTO tbl_name [(col,...)] VALUES ({expr | DEFAULT},...), (...),...  
    [, select_expr ...]]
```

UPDATE

```
UPDATE table_reference  
    SET col1={expr1|DEFAULT} [,col2={expr2|DEFAULT}] ...  
    [WHERE where_condition]
```

DELETE

```
DELETE FROM tbl_name  
    [WHERE where_condition]
```

PREPARED STATEMENTS

```
PREPARE stmt_name FROM preparable_stmt  
EXECUTE stmt_name [USING expression, ...]
```

TRANSACTIONS

```
START TRANSACTION | BEGIN [WORK]  
COMMIT [WORK]  
ROLLBACK [WORK]
```

STORED PROCEDURE

```
DELIMITER //
CREATE [OR REPLACE] PROCEDURE [IF NOT EXISTS] sp_name ([proc_parameter[, ...]])
BEGIN
    ...
END//
DELIMITER ;
proc_parameter: [IN | OUT | INOUT] param_name datatype
CALL sp_name([param_1[, ...]])
```

FUNCTION

```
DELIMITER //
CREATE [OR REPLACE] FUNCTION [IF NOT EXISTS] func_name ([func_parameter[, ...]])
RETURNS datatype
BEGIN
    ...
END//
DELIMITER ;
func_parameter: param_name datatype
```

TRIGGER

```
DELIMITER //
CREATE [OR REPLACE] TRIGGER [IF NOT EXISTS] trigger_name [BEFORE | AFTER] [INSERT |
UPDATE | DELETE] ON tbl_name FOR EACH ROW
BEGIN
    ...
END//
DELIMITER ;
```

STATEMENTS

```
DECLARE var_name datatype [DEFAULT value]
SET var_name = value
IF condition THEN statements [ELSE | ELSEIF condition THEN statements] END IF
CASE expression WHEN value_1 THEN statements [WHEN value_2 THEN statements | ELSE
statements] END CASE
CASE WHEN condition_1 THEN statements [WHEN condition_2 THEN statements | ELSE
statements] END CASE
WHILE condition DO statements END WHILE
REPEAT statements UNTIL condition END REPEAT
FOR var_name IN [REVERSE] lower_bound .. upper_bound DO statements END FOR
RETURN value
```

DATATYPES

```
INT Ganzzahliger Wert
DECIMAL(x, y) Fließkommazahl mit x Stellen, davon y Nachkommastellen
CHAR(x) Zeichenkette mit x Zeichen
VARCHAR(x) Variable Zeichenkette mit maximal x Zeichen
DATE Datumswert im Format yyyy-mm-dd
DATETIME Datums-/Zeitwert im Format yyyy-mm-dd hh:nn:ss
```